

# imageRUNNER

ADVANCE

715iF/715iFZ 615iF/615iFZ 525iF/525iFZ



## imageRUNNER ADVANCE 715iF III Series

Black-and-White | Compact | Multifunction

Print up to 75 ppm (BW)

Scan up to 100 ipm (300 dpi) (BW/color, duplex)

Print up to 8-1/2" x 14"

3,300-sheet maximum paper capacity

Canon's comprehensive portfolio of imageRUNNER ADVANCE multifunction printers and integrated solutions can help **simplify** the end user experience and management of technology; better **control** sensitive information and print-related costs; and help ensure that technology investments proactively **evolve** with changing needs.



- 10.1" intuitive touchscreen with smartphone-like usability.
- A unique, customized experience tailored to individual preferences using My ADVANCE.
- Supports mobile solutions and integration with many popular cloud services like Google Drive and Box.<sup>1</sup>
- Scan and convert documents to searchable digital files in a variety of file formats.
- Integration with Canon and various third-party software with embedded application platform.



## **SECURITY**

- Advanced standard security feature set to help safeguard sensitive information and assist in regulatory compliance.
- Integrates with existing, third-party Security Information and Event Management (SIEM) systems to help provide real-time comprehensive insights into potential threats to the network and printers.
- Technology to verify that the device boot process, firmware, and applications initialize without alterations or tampering.
- Security policy settings can be controlled with a dedicated password, configured from a central location, and exported to other supported devices.
- Control access to the device and specific features, using a host of flexible authentication methods—PIN code, user name/password, or card access.<sup>2</sup>



# QUALITY AND RELIABILITY

- Canon's signature reliability and engine technologies help keep productivity high and minimize the impact on support resources.
- Outstanding imaging technologies and toner allow for crisp text and consistent images in rich black-and-white tones.
- Designed to achieve maximum uptime with status notifications to help keep supplies replenished and intuitive maintenance videos for consumables replacement.
- imageRUNNER ADVANCE models have received many awards and recognition from leading industry analysts, often referencing strong reliability.



- Designed for quick, easy deployment.
- Remote diagnostics and parts life management for proactive maintenance and rapid fixes.
- Easy and intuitive to monitor device status and consumable levels, turn off devices remotely, observe meter readings, manage settings, and implement security policies.
- Common firmware and regular updates with Unified Firmware Platform (UFP) for continuous improvements and consistency across a fleet.



- Track and assess print, copy, scan, and fax usage and allocate costs to departments or projects.
- Apply print policies and restrict usage by user to help reduce unnecessary printing and contribute to cost efficiency.
- Standard cloud-based solution provides a centralized dashboard with up-to-theminute insights into printer activity.
- Upgrade to uniFLOW server or cloud-based solutions for full accounting and reporting for compatible Canon and third-party devices, pull printing, job routing, and powerful scan workflows.



- A combination of fusing technologies and low-melting-point toner minimizes power requirements and helps achieve low energy consumption.
- Encourage environmentally-conscious work practices by enabling multiple settings that can help save paper and energy.
- ENERGY STAR® certified and rated EPEAT® Gold.³

## **CONFIGURATION OPTIONS**

## Standard Model (715iF III/615iF III/525iF III)\*



#### Finisher Model (715iFZ III/615iFZ III/525iFZ III)





#### **CASSETTE FEEDING UNIT-AR1**

- 550-sheet capacity and cabinet for storage
- · Supports up to Legal
- Supports 60 to 135 g/m<sup>2</sup>



#### HIGH CAPACITY CASSETTE FEEDING UNIT-D1

- 2,550-sheet capacity (550-sheet upper cassette, 2,000-sheet lower cassette)
- Supports up to Legal
- Supports 60 to 135 g/m<sup>2</sup>



#### CASSETTE MODULE-AG1\*\*

- 550-sheet capacity
- Supports up to Legal
- Supports 60 to 135 g/m<sup>2</sup>

#### **ENVELOPE CASSETTE MODULE-A1**

- 75-sheets (Envelope)
- Supports COM10 (No.10), Monarch, DL, ISO-C5
- Supports  $80 \text{ to } 100 \text{ g/m}^2$



#### CABINET TYPE-U▲▲

 Provides base (with wheels) for cassettes

- \* Finisher cannot be added after purchase.
- \*\* Can add up to three additional cassettes. When a combined total of three Cassette Module-AGI/Envelope Cassette Module-AI units are added to a finisher model. Cabinet Type-U is required.
- units are added to a finisher model, Cabinet Type-U is required.

  Maximum of two Envelope Cassette Module-Al units can be configured and only as the first or second additional cassette.
- ^^ Cabinet Type-U is required when three additional cassettes are added to a finisher model

## **SPECIFICATIONS**

#### Main Unit

Type

Monochrome Laser Multifunction

Core Functions

Print, Copy, Scan, Send, Fax

Processor

Canon Dual Custom Processor (Shared)

Control Panel

10.1" WSVGA Color Touch-panel

Memory

3.0 GB RAM

Hard Disk Drive

250 GB

Interface Connection

1000Base-T/100Base-TX/10Base-T, Network Wireless LAN (IEEE 802.11 b/g/n) Optional: NFC, Bluetooth Low Energy

Others

Standard USB 2.0 x2 (Host), USB 3.0 x1 (Host),

USB 2.0 x1 (Device) Copy Control Interface Optional: Paper Capacity (LTR, 20 lb. Bond) Standard: 650 Sheets

Maximum: 3,300 Sheets Paper Sources (LTR, 20 lb. Bond)

550-sheet Paper Cassette, 100-sheet Stack Standard:

Optional: 550-sheet (CASSETTE FEEDING UNIT-AR1),

2,650-sheet (HIGH CAPACITY CASSETTE FEEDING UNIT-D1), 550-sheet (CASSETTE MODULE-AG1), 75-envelope (ENVELOPE

CASSETTE MODULE-A1)

Paper Output Capacity (LTR, 20 lb. Bond)

Standard Model: 500 Sheets Finisher Model: 1,000 Sheets **Finishing Capabilities** 

Standard Model: Collate, Group

Finisher Model: Collate, Group, Offset, Staple

Supported Media Types

Thin, Plain, Recycled, Color, Heavy, Cassettes: Labels, Bond, Pre-punched Stack Bypass: Thin, Plain, Recycled, Color, Heavy,

Transparency, Bond, Envelope

Supported Media Sizes

Cassette (Std.): Letter, Executive, Statement, Custom size

(3-7/8" x 5-7/8" to 8-1/2" x 11-3/4")

Cassettes (Opt.): Legal, Letter, Executive, Statement. Custom size (3-7/8" x 5-7/8" to 8-1/2 x 14")

Legal, Letter, Executive, Statement, Stack Bypass:

Envelope [No.10 (COM10), Monarch, DL, ISO-C5], Custom size (3"  $\times$  5" to 8-1/2" x 14")

Supported Media Weights

16 lb. Bond to 36 lb. Bond (60 to 135 g/m<sup>2</sup>) Cassette: Stack Bypass: 16 lb. Bond to 74 lb. Cover (60 to 199 g/m²) Duplex: 16 lb. Bond to 32 lb. Bond (60 to 120 g/m<sup>2</sup>)

Print/Copy Speed (BW)

715iF III/715iFZ III: Up to 75 ppm (Letter); Up to 59 ppm (Legal) 615iF III/615iFZ III: Up to 65 ppm (Letter); Up to 51 ppm (Legal)

525iF III/525iFZ III: Up to 55 ppm (Letter); Up to 45 ppm (Legal)

Warm-up Time

From Power On: 30 Seconds or Less<sup>4</sup> From Sleep Mode: 10 Seconds or Less<sup>5</sup>

Quick Startup 4 Seconds or Less<sup>6</sup> Mode:

Dimensions (W x D x H)

Standard Model: 20-1/4" x 23-5/8" x 24-1/4" (513 mm x 601 mm x 617 mm)

20-1/4" x 23-5/8" x 32-1/8" Finisher Model:

(513 mm x 601 mm x 814 mm)

Dimensions (W x D x H) with Paper Feeding Unit or High Capacity Paper Feeding

Standard Model: 25-1/4" x 26-3/8" x 42-1/4" (642 mm x 668 mm x 1073 mm)

25-1/4" x 26-3/8" x 50" Finisher Model: (642 mm x 668 mm x 1270 mm)

Installation Space (W x D)

41-3/8" x 32-3/8" (1,052 mm x 823 mm)

Weight7

Standard Model: Approx. 81.6 lb. (37 kg) Finisher Model: Approx. 101.4 lb. (46 kg)

**Print Specifications** 

Print Resolution (dpi)

1200 x 600

Standard Page Description Languages

UFR II, PCL®6, Adobe® PS® 3

Direct Print

Available from USB, Advanced Box, Remote UI,

and Web Access8

Supported File Types

PDF, TIFF, JPEG, EPS, XPS

Printing from Mobile Devices and Cloud-based Services

A range of software and MEAP-based solutions are available to provide printing from compatible mobile devices or Internet-connected devices and cloud-based services depending on your requirements.9

Fonts

93 Roman, 10 Bitmap fonts, 2 OCR fonts, PCI fonts

Andalé Mono WT J/K/S/T (Japanese, Korean, Simplified and Traditional Chinese),<sup>10</sup>

Barcode Fonts<sup>11</sup>

PS fonts: 136 Roman

Operating System<sup>12</sup>

UFRII/PS Windows® 7/8.1/10, Windows Server

2008/2008 R2/2012/2012 R2/2016,

MAC OS X (10.9 or later)

PCL: Windows® 7/8.1/10, Windows Server 2008/2008 R2/2012/2012 R2/2016 PPD:

Windows® 7/8.1/10, MAC OS X (10.3.9

or later)

Copy Specifications

First-Copy-Out Time (LTR)

As fast as 5 Seconds

Copy Resolution (dpi)

600 x 600

**Multiple Copies** 

Up to 9,999

Magnification 25%-400% (1% Increments)

**Preset Reductions** 

25%, 50%, 64%, 78%

**Preset Enlargements** 

129%, 200%, 400%

**Basic Copy Features** 

Preset Reduction/Enlargement Ratios by Area, Paper Setting, Previous Settings, Favorite Settings, Finishing, Twosided, Density Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel

Special Copy Features

Two-sided Original, Finishing, Job Build, N on 1, Different Size Originals,13 Density Adjustment, Original Type Selection, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Job Done Notice, Copy ID Card, Skip Blank Pages, Multi Sheet Feed Detection

Scan Specifications

Single-pass Duplexing Automatic Document Feeder<sup>14</sup>

**Document Feeder Paper Capacity** 

100 Sheets (20 lb. Bond)

**Document Feeder Supported Media Sizes** 

Legal, Letter, Statement

Custom size: 4-1/8" x 5-7/8" to 8-1/2" x 14"

Document Feeder Supported Media Weights

12 lb. Bond to 33 lb. Bond (42 to 128 g/m²) BW Original: Color Original: 17 lb. Bond to 33 lb. Bond (64 to 128 g/m²)

Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects [Height up to 1-1/4"; Weight Up to 4.4 lb. (2 kg)]

Pull Scan

Color Network ScanGear2 for both Twain and WIA

Supported OS: Windows 7/8.1/10/

Server 2008/Server 2008 R2/

Server 2012/Server 2012 R2/Server 2016

Scan Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to mobile devices or cloud-based services depending on your requirements.

Scan Speed (LTR)

Single-sided Scanning

Color/BW: 50 ipm/50 ipm (300 dpi, send) BW: 50 ipm (600 dpi, copy)

Double-sided Scanning

Color/BW: 100 ipm/100 ipm (300 dpi, send)

100 ipm (600 dpi, copy)

Send Specifications

Destination

Email/Internet Fax (SMTP), SMB, FTP, Standard:

WebDAV, Mail Box, Super G3 Fax

Optional IP Fax

Address Book LDAP (2,000)/Local (1,600)/Speed Dial (200)

Send Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200,

200 x 100, 150 x 150, 100 x 100

Communication Protocol

FTP (TCP/IP), SMB v3.0, WebDAV

Email: SMTP. PÓP3

File Format

TIFF, JPEG, PDF (Compact, Searchable, Standard:

Apply Policy, Optimize for Web, PDF A/1-b, Encrypted, Device Signature), XPS (Compact, Searchable, Device Signature), Office Open XML (PowerPoint®, Word)

Optional: PDF (Trace & Smooth, User Signature), XPS (User Signature)

Multi Sheet Feed Detection

**Universal Send Features** Original Type Selection, Two-sided Original, Different-size Originals, <sup>13</sup> Density Adjustment, Sharpness, Erase Frame, Job Build, Sender's Name (TTI), Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-To, Email Priority, TX Report, Original Content Orientation, Skip Blank Pages,

### Fax Specifications

Maximum Number of Connection Lines

Modem Speed

33.6 Kbps Super G3: G3: 14.4 Kbps

Compression Method MH, MR, MMR, JBIG Resolution (dpi)

400 x 400, 200 x 400, 200 x 200, 200 x 100

Sending/Recording Size Statement to Legal Fax Memory Up to 30,000 Pages

Speed Dials Max. 200

Group Dials/Destinations

Max. 199 Dials

Sequential Broadcast Max. 256 Addresses Memory Backup

Fax Features

Original Type Selection, Two-sided Original, Density for Scanning, Sharpness, Erase Frame, Job Build, Sender's Name (TTI), Selecting the Telephone Line, Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Multi Sheet Feed Detection

## **Store Specifications**

Mail Box Simple (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored

Advanced Box

Communication Protocol: SMB or WebDAV

Supported

Client PC: Windows (Windows 7/8.1/10)

Concurrent Connections (Max.) SMB: 64

WehDAV-3 (Active Sessions)

Advanced Box Available Disc Space

Approx. 16 GB

**Advanced Box Features** 

Authentication for Advanced Box Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support

Memory Media

Standard: USB

## Security Specifications

Authentication

Universal Login Manager (Device and Standard-

Function Level Log-in), User Authentication, Department ID Authentication, Access Management System, uniFLOW

Online Express<sup>15</sup> uniFLOW

Optional:

Data

Standard: Trusted Platform Module (TPM),

Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2

Validated), Verify System at Startup IEEE 2600 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)

Network

Optional:

Standard: IP/Mac Address Filtering, IPsec, TLS

Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME, SIEM

Integration

Document

Secure Print, Adobe LiveCycle® Rights Standard

Management ES2.5 Integration, Encrypted PDF, Encrypted Secure Print, Device Signature, Secure Watermark

Ontional-User Signature

#### **Environmental Specifications**

Operating Environment

Temperature: 50 to 86° F

20 to 80% RH (Relative Humidity) Humidity:

Power Requirements 120-127V, 60 Hz, 9.7 A Plug (Main Unit) **NEMA 5-15P** 

**Power Consumption** 

Maximum: Approx. 1,500 W Standby: Approx. 29.77 W16 Sleep Mode: Approx. 1.0 W17

Typical Electricity Consumption (TEC) Rating:18

715iF III/715iFZ III: 3.1 kWh 615iF III/615iFZ III: 2.5 kWh 525iF III/525iFZ III: 2.1 kWh

Standards

ENERGY STAR® Certified Rated EPEAT® Gold3

## Consumables

T03 Black (All-in-One Toner Cartridge)19

Toner Yield20

51,500 Images

- Subscription to a third-party cloud service required. Subject to third-party cloud service providers' terms and conditions.
- Requires additional option.
- 3 For current EPEAT rating (Gold/Silver/Bronze),
- please visit www.epeat.net.
  Time from device power-on until copy ready (not print reservation).
- Time from exiting sleep mode to when printing is operational.
- Time from device power-on to when copy icon appears on the main menu of touch-panel.
- Includes consumables
- 8 PDF print from Web sites is supported.
- <sup>9</sup> For more information, including compatibility, please
- visit https://www.usa.canon.com/mobile-app.

  Requires the optional PCL International Font Set-A1.
- Requires the optional Barcode Printer Kit-D1.
- Other operating systems and environments including AS/400, UNIX, Linux and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.
- 13 Only for Letter/Legal.
- <sup>14</sup> Detect Feeder Multi Sheet Feed is supported.
- 15 No charge for this solution; however activation is required.
- <sup>16</sup> Reference value (measured one unit).
  <sup>17</sup> 0.41 W sleep mode not available in all circumstances due to certain settings.
- 18 Based on ENERGY STAR Product Specification for Imaging Equipment Version 2.0.
- 19 Includes toner, drum, developer, and waste toner hopper.
- <sup>20</sup> Toner cartridge yield in accordance with ISO/IEC 19752.

For detailed specifications and a comprehensive list of optional accessories, see the imageRUNNER ADVANCE 715iF III Series Specifications document.





601 S. SAN GABRIEL BLVD. SAN GABRIEL, CA 91776 (888) 405-9888

www.copyfree.com















As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. AirPrint and the AirPrint logo are trademarks of Apple Inc. Canon, imageRUNNER, imageWARE, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. CUSA, through its subsidiary CIIS, has strategic partnerships with Box and mxHero. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Print speed is based on internal testing. Print speed may vary depending on the number of copies selected, as well as on the settings for size, type, and orientation of paper. Canon doe's not warrant that use of its features will prevent security issues. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Products shown with optional accessories. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors ©2019 Canon U.S.A., Inc. All rights reserved.

To learn about Canon's many awards, visit usa.canon.com/awards.











